

HIGH SPIN WASHER EXTRACTORS

IPH180 H

IPH270 H

IPH370 H

IPH460 H

IPH570 H

IPH640 H

IPH790 H



IPSO

TECHNICAL SPECIFICATIONS IHP 180 - 270 - 370 - 460 - 570 - 640 - 790 H

		IHP180 H	IHP270 H	IHP370 H	PH460 H	IPH570 H	IPH640 H	IPH790 H					
Cylinder	Capacity (kg)	17,8	27,2	37	45,9	57	64,3	79,5					
	Capacity (lbs)	39,3	60	81,6	101	125	141,7	175					
	Volume (L)	178,3	271,7	370,7	458,5	569,2	642,4	759,9					
	Diameter (mm)	686	787	940	940	1092	1092	1092					
	Depth (mm)	483	559	533	660	610	686	813					
	Perforations diam. (mm)	4,83	4,83	4,83	4,83	4,83	4,83	4,83					
Door opening diam. (mm)		381	432	508	508	622	622	622					
Low wash speed	G-Force	0,014	0,016	0,019	0,019	0,022	0,022	0,022					
	rpm	6	6	6	6	6	6	6					
Wash speed	G-Force	0,8	0,8	0,8	0,8	0,8	0,8	0,8					
	rpm	46	43	39	39	36	36	36					
Balance speed	G-Force	2	2	2	2	2	2	2					
	rpm	72	67	62	62	57	57	57					
Low extraction speed	G-Force	100	100	100	100	100	100	100					
	rpm	511	477	437	437	405	405	405					
Medium extraction speed	G-Force	140	140	140	140	140	140	140					
	rpm	605	564	516	516	479	479	479					
High extraction speed	G-Force	230	230	230	230	200	200	200					
	rpm	775	723	662	662	573	573	573					
Maximum extraction speed	G-Force	300	300	300	300	300	250	250					
	rpm	885	826	756	756	701	640	640					
	Power motor (kW)	2,3	3,7	5,6	5,6	7,5	5,6	11,2					
Diameter drain (mm)		75 (3")	75 (3")	75 (3")	75 (3")	75 (3")	75 (3")	75 (3")					
Weight	Nett. (kg)	768,2	815,9	875,5	985	1247	1375,9	1489,5					
	Gross (kg)	804,5	861,3	920,9	1030,5	1292	1421,3	1535					
Dimensions	Height (mm)	1448	1590	1778	1778	1958	1958	1958					
	Width (mm)	813	876	1080	1080	1430	1430	1430					
	Depth (mm)	1158	1213	1306	1433	1425	1502	1626					
Packing Volume (m ³)		1,78	2,18	3,11	3,45	4,53	4,73	5,16					
Type of heating		POWER SUPPLY – FUSES											
		230V	380V	230V	380V	230V	380V	230V	380V	230V	380V	230V	380V
Boiler Fed / Steam		16	16	16	16	20	16	20	16	32	16	32	16
Electrical heating		63	32	125	32	125	32	125	63	-	-	-	-

